

## SI Rod end BEF05-20-501-DURBAL - BEF05-20-501-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/bef05-20-501-durbal>

### BEF05-20-501



**rod end housing:**  
forged steel, tempered, surface galvanized, free of Cr-VI


**joint ball:**  
ball bearing steel, hardened and ground, surface superfinished and chromium plated

**race:**  
nylon / teflon / glass fibre compound

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral spherical plain bearing**

**female thread:**  
maintenance free, adapter sizes according to DIN ISO 12240-4, series K, thread according to ISO 8139



order number		measurements [mm]																				
type	right-hand thread	left-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	d <sub>8</sub>	h	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating dyn. C [N]	stat. C <sub>0</sub> [N]	
BEF 05	-20	-501		5	9,0	M 5		18	11	11,06	8	6,0										
type	h	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating		dyn. C [N]		stat. C <sub>0</sub> [N]								
BEF 05	27	10	4,0	10	9			13,0	7,5	0,018	3910		10800									

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507989
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	18 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE