

## SI Rod end BEF22-20-502-DURBAL - BEF22-20-502-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/bef22-20-502-durbal>

### BEF22-20-502



**rod end housing:**  
forged steel, tempered, surface galvanized, free of Cr-VI


**joint ball:**  
ball bearing steel, hardened and ground, surface superfinished and chromium plated

**race:**  
nylon / teflon / glass fibre compound

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral spherical plain bearing**

**female thread:**  
maintenance free, adapter sizes according to DIN ISO 12240-4, series K, thread according to ISO 8139



order number		measurements [mm]																				
type	right-hand thread	left-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	d <sub>8</sub>	h	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating dyn. C [N]	stat. C <sub>0</sub> [N]	
BEF 22	-20	-502	22	30,0	M 22 x 1,5	54	38	38,05	28	20,0												
type	h	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating dyn. C [N]	stat. C <sub>0</sub> [N]											
BEF 22	84	37	12,0	26	32		15,5	10,0	0,520	38230	95600											

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952508221
Inside diameter	22 mm
Outside diameter	54 mm
Thickness	28 mm
Type	SI
Weight	520 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE