

SI Rod end BRF10-60-502-DURBAL - BRF10-60-502-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/si/brf10-60-502-durbal>

BRF10-60-502



rod end housing:
stainless steel 1.4534, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]											
type	light hand thread	light hand thread	M 10	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h
BRF 10 -60		-502		10	15,0	M 10	12,0	28	19	14	10,5	43	
measurements [mm]		weight	calculation-factors	rotational speed limit	basic load rating								
type	l	l ₁	l ₂	SW	α [°]	[kg]	Y	v ₀	speed limit [min]	C	dyn. [N]	stat. C ₀ [N]	1000
BRF 10	20	6,5	15	17	8,0	0,072	1,90	1,81	1225		3100	1000	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952509259
Inside diameter	10 mm
Outside diameter	28 mm
Thickness	14 mm
Type	SI
Weight	72 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE