


# SA Rod end


## BRTM1-1-00-502-DURBAL - BRTM1-1-00-502-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/brtm1-1-00-502-durbal>

**BRTM1/1-00-502** 

male thread:  
long-term  
lubrication,  
low maintenance,  
shields,  
dimensions in inches

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
roller bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminum-complex-soap-grease,  
temperature range -45 °C to +120 °C,  
approval according to USDA H1

lubrication fitting:  
DIN 71 412 H1

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [inches]										
type	right-hand thread	left-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	
BRTM 1/1 -00		-502	1.000	1.0000-12 UNF	1.161	2.519	1.220	.866				
		measurements [inches]							weight	rotational speed limit	basic load rating	
type	h	l	l <sub>2</sub>	α	α'	weight	rotational speed limit	basic load rating	dyn.	stat.		
BRTM 1/1	3.720	2.264	1.279	5,0		0.590	600	24900	18500			

### PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952509952
Inside diameter	25.4 mm
Outside diameter	63.98 mm
Thickness	30.99 mm
Type	SA
Weight	590 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)  
+1(646) 712 9672  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE