



# SA Rod end BRTM1-1-01-501-DURBAL - BRTM1-1-01-501-DURBAL

<https://www.123bearing.ca/bearing-housing/rod-end/sa/brtm1-1-01-501-durbal>

**BRTM1/1-01-501** 

male thread:  
long-term  
lubrication,  
low maintenance,  
shields,  
dimensions in inches

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
roller bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminum-complex-soap-grease,  
temperature range -45 °C to +120 °C,  
approval according to USDA H1

lubrication fitting:  
DIN 71 412 H1

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [inches]								
type	right-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>
BRTM 1/1	-01	-501	1.000	1.0000-14 UNS	1.161	2.519	1.220	.866		
		measurements [inches]			weight	rotational speed limit rpm [min <sup>-1</sup> ]	basic load rating dyn. C [N]		stat. C <sub>0</sub> [N]	
type		h	l	l <sub>2</sub>	α [°]	[kg]				
BRTM 1/1		3.720	2.264	1.279	5,0	0.590	600	24900	18500	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952509983
Inside diameter	25.4 mm
Outside diameter	63.98 mm
Thickness	30.99 mm
Type	SA
Weight	590 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE