

## Drawn cup roller bearing FCL-10-K-NADELLA - FCL-10-K-NADELLA

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/drawn-cup/fcl-10-k-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F <sub>2</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
10	FCL-10-K	10	14	12	4.60	19000	HK1010

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
10	13.980	9.976	10.005	20	10.000	9.994	13.991	13.980	0.004

## PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3616060472519
Inside diameter	10 mm
Outside diameter	14 mm
Thickness	12 mm
Weight	4 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE