


## Deep groove ball bearing single row 7508-DL-NICE - 7508-DL-NICE

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/single-row/7508-dl-nice>

**7500 Series™ Heavy Duty Precision Ground Radial Bearings** **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - IDEAL FOR THE MOST DEMANDING APPLICATIONS
- EASY TO USE MICH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE - HIGH RPM
- THROUGH HARDENED BEARING STEEL
- POLISHED FINISH
- WIDE RETAINING STANDARDS
- DOUBLE SEALED VERSIONS
- SPECIAL OPERATING MODES - IN CONTACT WITH OTHER BEARINGS
- AVAILABLE WHILE STOCKED OR ORDER
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO ORDER
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION ARE CONCERNS



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7508™	+0.000 -0.005 -0.013	+0.000 -0.005 -0.013	+0.000 -0.005 -0.013	0.0625 1.58	7500 19.05	1.009 25.63

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	A (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.136 3.45	0.042 1.07	1.9219 48.82	0.035 0.89	8595 11548	1025 4581	0.33 0.15	0.750 19.05	1.500 38.10	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLQ)  
 ② Tolerance for 7514™ and larger is +0.000/-0.006 (+.000/-0.15)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of FSC Nide® Bearings.

## PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473271
Inside diameter	12.7 mm
Outside diameter	44.45 mm
Thickness	15.88 mm
Weight	150 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE