


Deep groove ball bearing single row 400-18V-NICE - 400-18V-NICE

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/single-row/400-18v-nice>

400 Series® Single Row. Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	18V	0.375 9.53 +0.0005-0.0008 -0.13-0.00	1.062 26.97 +0.0050-0.0000 -0.13-0.00	0.375 9.53 +0.0110-0.0110 -0.25-0.25	0.375 9.53 Reference	16	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
	(N)	(N)	(N)	(N)	(N)	(N)
0.05	178	124	85	69	48	34
0.05	792	552	378	307	214	151

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560038
Inside diameter	9.53 mm
Outside diameter	26.97 mm
Thickness	9.53 mm
Weight	20 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE