

Deep groove ball bearing single row 602-V-NICE - 602-V-NICE

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/single-row/602-v-nice>

600 Series™ Unground Thrust Bearings **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- POLY-STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE

BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in)	BORE (in)	O.D. (in)	HEIGHT (in)		
602™	V	.375 9.53	+.010 10.15	1.394 26.59	-.359 9.12	No. 14 Size 5/32	0.06 0.03

THRUST CAPACITY						
REVOLUTIONS PER MINUTE						
10	50	100	250	500	1000	
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(N)
426	344	254	138	100	71	
1896	1531	1130	614	445	318	

Notes
 Balls - Carbon Steel Grade 520
 Washers - Carbon Steel Case Hard
 Bands - Carbon Steel Soft
 Bearings Oiled with a Rust Preventative
 All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560342
Inside diameter	9.53 mm
Outside diameter	26.59 mm
Thickness	9.12 mm
Weight	30 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE