

## Housed bearing accessorie 7620-DL-NICE - 7620-DL-NICE

<https://www.123bearing.ca/bearing-housing/housed-bearing/accessories/7620-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)** **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- GRADE 5 STEEL
- WATER WASH RESISTANT
- SHOCK RESISTANT
- SEALY APPROXIMATE ANGULAR CONTACT
- AVAILABLE IN SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS UNLESS OTHERWISE NOTED
- RECOMMENDED FOR APPLICATIONS WHERE EXCELLENT RIGIDITY IS REQUIRED

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7620™ Ø	1.2500 31.75	2.5425 64.78	0.7500 19.05	0.0625 1.59	1.872 42.47	0.190 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R R (in) (mm)	Dynamic C (Db)	Static C <sub>0</sub> (Db)	W (kg)
0.065 1.65	2.768 70.25	1.417 35.98	1.417 35.98	0.605 15.37	0.261 6.63	1/4-28 0.089 2.26	5360 23852	2620 11659	0.71 0.32

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)  
 ② Tolerance for 7613™ and larger is +.0000/-0.0006 (+.0001/-0.015)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of NICE Bearings.

## PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473509
Inside diameter	31.75 mm
Outside diameter	42.47 mm
Thickness	19.05 mm
Weight	320 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE