

SI Rod end FXL-08-G-DUNLOP - FXL-08-G-DUNLOP

<https://www.123bearing.ca/bearing-housing/rod-end/si/fxl-08-g-dunlop>

FEMALE ROD ENDS

FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: 817M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged 817M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

| Part No. Right Hand | Part No. Left Hand | D | W | H | O | D | F | A | J | M | X | Static Load Rating (Newton) Radial |
|---------------------|--------------------|------|-----|-----|-----|-------|-------|-------|------|---------|----|------------------------------------|
| FXL-08FG | | 5000 | 750 | 640 | 750 | 1.625 | 2.125 | 1.125 | .800 | 1/2 BSF | 22 | 49000 |

Interchange table

| Dunlop | Rose | NMB |
|---------------|-------|-------|
| FX-M (metric) | RBJ-M | RBJ-M |
| FX (imperial) | RBJ | RBJ |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DUNLOP |
| N° Ean13 | 3616060556059 |
| Inside diameter | 5000 mm |
| Outside diameter | 750 mm |
| Thickness | 640 mm |
| Type | SI |
| Thread | Right-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE