

SI Rod end AL-SA-082-LH-DUNLOP - AL-SA-082-LH-DUNLOP

<https://www.123bearing.ca/bearing-housing/rod-end/si/al-sa-082-lh-dunlop>

FEMALE ROD ENDS

AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminium A6061, black anodised. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

<p>Features</p> <ul style="list-style-type: none"> Metric bore & thread sizes Low friction Self-lubricating Good wear resistance Excellent moisture resistance No maintenance Light weight 	<p>Possible Applications</p> <ul style="list-style-type: none"> Light industrial/mechanical applications Weight restricted applications Linear movement sensors 	<p>Temperature Range</p> <p>-30°C to +170°C</p> <p>Specification</p> <p>ELV & RoHS compliant</p>
--	---	--

Housing: Aluminium A6061, Black Anodised

Race Ball: GR-nylon, LV-3H Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-082LH		8	M8x1.25	12	9.00	22	36.0	16.0	10.4	14.0	7,720

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556547
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	12 mm
Outside diameter	0.472" inch
Thickness	9 mm
Thickness	0.354" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE