


GE Rod end GE304-ES-DUNLOP - GE304-ES-DUNLOP

<https://www.123bearing.ca/bearing-housing/rod-end/ge/ge304-es-dunlop>

SPHERICAL BEARINGS




GEZ ES SERIES

Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Balls: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seats: Polyurethane

Part No. Unscaled	Part No. Scaled	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE304ES		3-1/4	72.238	61.902	130.175	1,760,000

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558343
Inside diameter	82.55 mm
Outside diameter	130.175 mm
Thickness	72.23 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE