

GE Rod end GE308-ES-2RS-DUNLOP - GE308-ES-2RS-DUNLOP

<https://www.123bearing.ca/bearing-housing/rod-end/ge/ge308-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

GEZ ES SERIES



Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specification:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂. **Balls:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate. **Seals:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE308ES-2RS	3-1/2	77.775	66.675	139.700	2,040,000

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558350
Inside diameter	88.9 mm
Outside diameter	139.7 mm
Thickness	77.77 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE