

## Self aligning ball bearing 11308-FAG - 11308-FAG

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/sefl-aligning/11308-fag>



Dimensions		Dimensions de base	
d	40 mm	d	35.9 mm
D	90 mm	D <sub>2</sub>	79.2 mm
B	23 mm	r <sub>s</sub>	0.12 mm
A	87.47 mm	r <sub>e</sub>	0.09 mm
D <sub>1</sub>	86.2 mm	r <sub>r</sub>	0.12 mm
r <sub>1</sub>	1.1 mm	r <sub>1</sub>	0.25 mm
r <sub>2</sub>	1.1 mm	r <sub>2</sub>	0.25 mm
r <sub>3</sub>	1.1 mm	r <sub>3</sub>	0.25 mm
r <sub>4</sub>	1.1 mm	r <sub>4</sub>	0.25 mm
r <sub>5</sub>	1.1 mm	r <sub>5</sub>	0.25 mm
r <sub>6</sub>	1.1 mm	r <sub>6</sub>	0.25 mm
r <sub>7</sub>	1.1 mm	r <sub>7</sub>	0.25 mm
r <sub>8</sub>	1.1 mm	r <sub>8</sub>	0.25 mm
r <sub>9</sub>	1.1 mm	r <sub>9</sub>	0.25 mm
r <sub>10</sub>	1.1 mm	r <sub>10</sub>	0.25 mm
r <sub>11</sub>	1.1 mm	r <sub>11</sub>	0.25 mm
r <sub>12</sub>	1.1 mm	r <sub>12</sub>	0.25 mm
r <sub>13</sub>	1.1 mm	r <sub>13</sub>	0.25 mm
r <sub>14</sub>	1.1 mm	r <sub>14</sub>	0.25 mm
r <sub>15</sub>	1.1 mm	r <sub>15</sub>	0.25 mm
r <sub>16</sub>	1.1 mm	r <sub>16</sub>	0.25 mm
r <sub>17</sub>	1.1 mm	r <sub>17</sub>	0.25 mm
r <sub>18</sub>	1.1 mm	r <sub>18</sub>	0.25 mm
r <sub>19</sub>	1.1 mm	r <sub>19</sub>	0.25 mm
r <sub>20</sub>	1.1 mm	r <sub>20</sub>	0.25 mm
r <sub>21</sub>	1.1 mm	r <sub>21</sub>	0.25 mm
r <sub>22</sub>	1.1 mm	r <sub>22</sub>	0.25 mm
r <sub>23</sub>	1.1 mm	r <sub>23</sub>	0.25 mm
r <sub>24</sub>	1.1 mm	r <sub>24</sub>	0.25 mm
r <sub>25</sub>	1.1 mm	r <sub>25</sub>	0.25 mm
r <sub>26</sub>	1.1 mm	r <sub>26</sub>	0.25 mm
r <sub>27</sub>	1.1 mm	r <sub>27</sub>	0.25 mm
r <sub>28</sub>	1.1 mm	r <sub>28</sub>	0.25 mm
r <sub>29</sub>	1.1 mm	r <sub>29</sub>	0.25 mm
r <sub>30</sub>	1.1 mm	r <sub>30</sub>	0.25 mm
r <sub>31</sub>	1.1 mm	r <sub>31</sub>	0.25 mm
r <sub>32</sub>	1.1 mm	r <sub>32</sub>	0.25 mm
r <sub>33</sub>	1.1 mm	r <sub>33</sub>	0.25 mm
r <sub>34</sub>	1.1 mm	r <sub>34</sub>	0.25 mm
r <sub>35</sub>	1.1 mm	r <sub>35</sub>	0.25 mm
r <sub>36</sub>	1.1 mm	r <sub>36</sub>	0.25 mm
r <sub>37</sub>	1.1 mm	r <sub>37</sub>	0.25 mm
r <sub>38</sub>	1.1 mm	r <sub>38</sub>	0.25 mm
r <sub>39</sub>	1.1 mm	r <sub>39</sub>	0.25 mm
r <sub>40</sub>	1.1 mm	r <sub>40</sub>	0.25 mm
r <sub>41</sub>	1.1 mm	r <sub>41</sub>	0.25 mm
r <sub>42</sub>	1.1 mm	r <sub>42</sub>	0.25 mm
r <sub>43</sub>	1.1 mm	r <sub>43</sub>	0.25 mm
r <sub>44</sub>	1.1 mm	r <sub>44</sub>	0.25 mm
r <sub>45</sub>	1.1 mm	r <sub>45</sub>	0.25 mm
r <sub>46</sub>	1.1 mm	r <sub>46</sub>	0.25 mm
r <sub>47</sub>	1.1 mm	r <sub>47</sub>	0.25 mm
r <sub>48</sub>	1.1 mm	r <sub>48</sub>	0.25 mm
r <sub>49</sub>	1.1 mm	r <sub>49</sub>	0.25 mm
r <sub>50</sub>	1.1 mm	r <sub>50</sub>	0.25 mm
r <sub>51</sub>	1.1 mm	r <sub>51</sub>	0.25 mm
r <sub>52</sub>	1.1 mm	r <sub>52</sub>	0.25 mm
r <sub>53</sub>	1.1 mm	r <sub>53</sub>	0.25 mm
r <sub>54</sub>	1.1 mm	r <sub>54</sub>	0.25 mm
r <sub>55</sub>	1.1 mm	r <sub>55</sub>	0.25 mm
r <sub>56</sub>	1.1 mm	r <sub>56</sub>	0.25 mm
r <sub>57</sub>	1.1 mm	r <sub>57</sub>	0.25 mm
r <sub>58</sub>	1.1 mm	r <sub>58</sub>	0.25 mm
r <sub>59</sub>	1.1 mm	r <sub>59</sub>	0.25 mm
r <sub>60</sub>	1.1 mm	r <sub>60</sub>	0.25 mm
r <sub>61</sub>	1.1 mm	r <sub>61</sub>	0.25 mm
r <sub>62</sub>	1.1 mm	r <sub>62</sub>	0.25 mm
r <sub>63</sub>	1.1 mm	r <sub>63</sub>	0.25 mm
r <sub>64</sub>	1.1 mm	r <sub>64</sub>	0.25 mm
r <sub>65</sub>	1.1 mm	r <sub>65</sub>	0.25 mm
r <sub>66</sub>	1.1 mm	r <sub>66</sub>	0.25 mm
r <sub>67</sub>	1.1 mm	r <sub>67</sub>	0.25 mm
r <sub>68</sub>	1.1 mm	r <sub>68</sub>	0.25 mm
r <sub>69</sub>	1.1 mm	r <sub>69</sub>	0.25 mm
r <sub>70</sub>	1.1 mm	r <sub>70</sub>	0.25 mm
r <sub>71</sub>	1.1 mm	r <sub>71</sub>	0.25 mm
r <sub>72</sub>	1.1 mm	r <sub>72</sub>	0.25 mm
r <sub>73</sub>	1.1 mm	r <sub>73</sub>	0.25 mm
r <sub>74</sub>	1.1 mm	r <sub>74</sub>	0.25 mm
r <sub>75</sub>	1.1 mm	r <sub>75</sub>	0.25 mm
r <sub>76</sub>	1.1 mm	r <sub>76</sub>	0.25 mm
r <sub>77</sub>	1.1 mm	r <sub>77</sub>	0.25 mm
r <sub>78</sub>	1.1 mm	r <sub>78</sub>	0.25 mm
r <sub>79</sub>	1.1 mm	r <sub>79</sub>	0.25 mm
r <sub>80</sub>	1.1 mm	r <sub>80</sub>	0.25 mm
r <sub>81</sub>	1.1 mm	r <sub>81</sub>	0.25 mm
r <sub>82</sub>	1.1 mm	r <sub>82</sub>	0.25 mm
r <sub>83</sub>	1.1 mm	r <sub>83</sub>	0.25 mm
r <sub>84</sub>	1.1 mm	r <sub>84</sub>	0.25 mm
r <sub>85</sub>	1.1 mm	r <sub>85</sub>	0.25 mm
r <sub>86</sub>	1.1 mm	r <sub>86</sub>	0.25 mm
r <sub>87</sub>	1.1 mm	r <sub>87</sub>	0.25 mm
r <sub>88</sub>	1.1 mm	r <sub>88</sub>	0.25 mm
r <sub>89</sub>	1.1 mm	r <sub>89</sub>	0.25 mm
r <sub>90</sub>	1.1 mm	r <sub>90</sub>	0.25 mm
r <sub>91</sub>	1.1 mm	r <sub>91</sub>	0.25 mm
r <sub>92</sub>	1.1 mm	r <sub>92</sub>	0.25 mm
r <sub>93</sub>	1.1 mm	r <sub>93</sub>	0.25 mm
r <sub>94</sub>	1.1 mm	r <sub>94</sub>	0.25 mm
r <sub>95</sub>	1.1 mm	r <sub>95</sub>	0.25 mm
r <sub>96</sub>	1.1 mm	r <sub>96</sub>	0.25 mm
r <sub>97</sub>	1.1 mm	r <sub>97</sub>	0.25 mm
r <sub>98</sub>	1.1 mm	r <sub>98</sub>	0.25 mm
r <sub>99</sub>	1.1 mm	r <sub>99</sub>	0.25 mm
r <sub>100</sub>	1.1 mm	r <sub>100</sub>	0.25 mm

### PRODUCT FEATURES

Brand	FAG
N° Ean13	3616060692900
Inside diameter	40 mm
Outside diameter	90 mm
Thickness	23 mm
Limiting speed	9500 rpm
Dynamic load	33.8 kN
Static load	11.2 kN
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE