

## Glue

### 589-250ML-LOCTITE - 589-250ML-LOCTITE

<https://www.123bearing.ca/lubricant-adhesive/lubricant/glue/589-250ml-loctite>

|                        |                                |
|------------------------|--------------------------------|
| <b>TITRE</b>           | Anaérobie                      |
| <b>DESCRIPTION</b>     | Poréotanche, résistance élevée |
| <b>NOM</b>             | LOCTITE 589                    |
| <b>CONDITIONNEMENT</b> | Facon 250 ml                   |
| <b>COMMENTAIRE</b>     |                                |
| <b>APPROBATION*</b>    |                                |

#### Description

LOCTITE® 589 is a green, low-viscosity, dimethacrylate ester, acrylic, threadlocking adhesive. The product is used to lock and seal fine-threaded nuts, bolts and studs in a wide variety of applications. LOCTITE 589 is also used to seal porosity in welds, castings and powdered metal parts. Demonstrates high-strength capability.

#### Avantages

Ideal for fine-threaded nuts, bolts and studs  
 Suits a wide variety of applications  
 Also seals porosity in welds, castings and powdered metal parts  
 Positive fluorescence under UV light

#### Caractéristiques

Acrylic green threadlocker with high strength. Used on fine-threaded nuts, bolts and studs.

## PRODUCT FEATURES

|           |               |
|-----------|---------------|
| Brand     | LOCTITE       |
| N° Ean13  | 5010266589657 |
| Type      | ETANCHEITE    |
| Weight    | 200 g         |
| Packaging | 1             |
| Use       | Anaérobie     |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE