

Tapered roller bearing TRA0607-R-JTEKT - TRA0607-R-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/tra0607-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
30	72	20.75	19	16	56.9	55.6	5 900	7 900	TRA0607R					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{3a} min.	r _{3a} max.		Y ₁	Y ₀	
—	18.6	38.5	39	63.5	58	68	3	4.5	1.5	1.5	0.55	1.10	0.60	0.405

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400747
Inside diameter	30 mm
Outside diameter	72 mm
Thickness	20.75 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE