

Tapered roller bearing 32909-JR-JTEKT - 32909-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32909-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
45	68	15	15	12	34.7	52.4	5 300	7 100	32909JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		Y ₁	Y ₀				
29C	12.5	49.5	50	63.5	61	64	3	3	0.6	0.6	0.32	1.88	1.04	0.190

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952404974
Inside diameter	45 mm
Outside diameter	68 mm
Thickness	15 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE