

Tapered roller bearing 30316-R-JTEKT - 30316-R-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30316-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
80	170	42.5	39	33	3	2.5	277	330	2 300	3 100	30316R

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
—	33.9	94	102	158	148	159	4	9.5	2.5	2	0.35	1.73	0.95	4.26

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122231
Inside diameter	80 mm
Outside diameter	170 mm
Thickness	42.5 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE