

Tapered roller bearing 30317-D-JTEKT - 30317-D-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30317-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
85	180	44.5	41	28	231	255	1 900	2 600	30317D					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	56.0	103	103	166	143	169	6	16.5	3	2.5	0.81	0.74	0.41	4.54

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122262
Inside diameter	85 mm
Outside diameter	180 mm
Thickness	44.5 mm
Packaging	1
Standard	No standard

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE