

Tapered roller bearing 30318-DJR-JTEKT - 30318-DJR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30318-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|---------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|----------------------|----------------|----------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 90 | 190 | 46.5 | 43 | 30 | 288 | 350 | 1 700 | 2 400 | 30318DJR | | | | | |
| Dimension series to ISO355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | | | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | |
| 7GB | 59.6 | 108 | 109 | 176 | 151 | 179 | 6 | 16.5 | 3 | 2.5 | 0.83 | 0.73 | 0.40 | 5.57 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952409658 |
| Inside diameter | 90 mm |
| Outside diameter | 190 mm |
| Thickness | 46.5 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE