

# Tapered roller bearing 33220-JR-JTEKT - 33220-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/33220-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
100	180	63	63	48	431	680	2 100	2 800	33220JR					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3FE	45.7	114	112	168	151	172	10	15	2.5	2	0.40	1.48	0.82	6.92

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126727
Inside diameter	100 mm
Outside diameter	180 mm
Thickness	63 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE