

## Tapered roller bearing 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



| Boundary dimensions (mm)             |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                      |            |                    |                |                      |
|--------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|----------------------|------------|--------------------|----------------|----------------------|
| d                                    | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                      |            |                    |                |                      |
| 100                                  | 215                | 77.5                     | 73                   | 60                      | 4                    | 3                    | 579                  | 783                                  | 1 800                | 2 400                     | <b>32320JR</b>       |            |                    |                |                      |
| Dimension series to ISO95 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      |                           |                      | Constant e | Axial load factors |                | (Refer. 1) Mass (kg) |
|                                      |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | d <sub>2a</sub> min.    | d <sub>2a</sub> max. | D <sub>1a</sub> min. | D <sub>1a</sub> max. | S <sub>1a</sub> min.                 | S <sub>1a</sub> max. | r <sub>1a</sub> min.      | r <sub>1a</sub> max. |            | Y <sub>1</sub>     | Y <sub>0</sub> |                      |
| 26D                                  | 53.9               | 118                      | 123                  | 201                     | 177                  | 200                  | 8                    | 17.5                                 | 3                    | 2.5                       | 0.35                 | 1.74       | 0.96               | 13.0           |                      |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952410623 |
| Inside diameter  | 100 mm        |
| Outside diameter | 215 mm        |
| Thickness        | 77.5 mm       |
| Packaging        | 1             |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE