

Tapered roller bearing 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
100	215	77.5	73	60	4	3	579	783	1 800	2 400	32320JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	S _{2a} min.	S _{2a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀	
260	53.9	118	123	201	177	200	8	17.5	3	2.5	0.35	1.74	0.96	13.0	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410623
Inside diameter	100 mm
Outside diameter	215 mm
Thickness	77.5 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE