

# Tapered roller bearing 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm) |     |      |    | Basic load ratings (kN) |                |                 |             | Limiting speeds (min <sup>-1</sup> ) |       | Bearing No. <sup>1)</sup> |                |
|--------------------------|-----|------|----|-------------------------|----------------|-----------------|-------------|--------------------------------------|-------|---------------------------|----------------|
| d                        | D   | T    | B  | C                       | C <sub>r</sub> | C <sub>0r</sub> | Grease lub. | Oil lub.                             |       |                           |                |
| 100                      | 215 | 77.5 | 73 | 60                      | 4              | 3               | 579         | 783                                  | 1 800 | 2 400                     | <b>32320JR</b> |

  

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                      |                      |                      |                      |                      |                      | Constant e | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|--|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|------|
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min. | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min. | r <sub>1a</sub> max. |            | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 26D                                    | 53.9               | 118                      | 123                  | 201                  | 177                  | 200                  | 8                    | 17.5                 | 3                    | 2.5        | 0.35               | 1.74           | 0.96                 | 13.0 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952410623 |
| Inside diameter  | 100 mm        |
| Outside diameter | 215 mm        |
| Thickness        | 77.5 mm       |
| Packaging        | 1             |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE