

## Tapered roller bearing 32256-JTEKT - 32256-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32256-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>						
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.					
280	500	137	130	106	1860	3150	610	810	32256					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer.) Mass (kg)	
—	117.2	308	325	478	420	474	16	30	5	4	0.43	1.39	0.77	108

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412047
Inside diameter	280 mm
Outside diameter	500 mm
Thickness	137 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE