

Tapered roller bearing 33026-JR-JTEKT - 33026-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/33026-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
130	200	55	55	43	390	705	1 700	2 300	33026JR					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2EE	42.5	142	143	190	178	192	8	12	2	2	0.34	1.76	0.97	6.19

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126086
Inside diameter	130 mm
Outside diameter	200 mm
Thickness	55 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE