

Tapered roller bearing 32236-JR-JTEKT - 32236-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32236-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C _r	C _{0r}	Grease lub.	Oil lub.							
180	320	91	86	71	957	1 520	1 100	1 500	32236JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer.) Mass (kg)	
4GD	77.8	202	204	302	267	303	10	20	4	3	0.45	1.33	0.73	29.9

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124860
Inside diameter	180 mm
Outside diameter	320 mm
Thickness	91 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE