

## Tapered roller bearing 32238-JR-JTEKT - 32238-JR-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32238-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.							
190	340	97	92	75	5	4	1 090	1 740	1 000	1 300	<b>32238JR</b>				
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	S <sub>2a</sub> min.	S <sub>2a</sub> max.		r <sub>1a</sub> min.	r <sub>1a</sub> max.	
4GD	81.9	212	216	322	286	323	12	22	4	3	0.44	1.38	0.76	36.6	

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421537
Inside diameter	190 mm
Outside diameter	340 mm
Thickness	97 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE