

Tapered roller bearing 30340-JTEKT - 30340-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/30340-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C _{0r}	C _{0r}	Grease lub.	Oil lub.	
200	420	89	80	67	6	5	1120	1450	820	1100	30340

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	79.8	228	255	398	354	385	11	21	5	4	0.35	1.73	0.95	53.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421629
Inside diameter	200 mm
Outside diameter	420 mm
Thickness	89 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE