

# Tapered roller bearing L44640R-L44610-JTEKT - L44640R-L44610-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/l44640r-l44610-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
23.812	50.292	14.224	14.732	10.668	1.6	1.2	31.2	37.0	7 800	10 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
L44640R	L44610	10.8	30.5	28.5	44.5	47.0	1.6	1.2	0.37	1.60	0.88	0.099	0.034

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425559
Inside diameter	23.812 mm
Outside diameter	50.292 mm
Thickness	14.224 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE