

## Tapered roller bearing 17098-17244-JTEKT - 17098-17244-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/17098-17244-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
24.981	62.000	16.002	16.566	14.288	1.6	1.6	38.0	40.6	6 700	8 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
17098	17244	12.7	33.0	30.5	54.0	57.0	1.6	1.6	0.38	1.57	0.86	0.162	0.090

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425597
Inside diameter	24.981 mm
Outside diameter	62 mm
Thickness	16.002 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE