

Tapered roller bearing 07100S-07196-JTEKT - 07100S-07196-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/07100s-07196-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
25.400	50.005	13.495	14.280	9.525	1.6	1.0	26.7	28.8	7 900	11 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
07100S	07196	10.8	31.5	29.5	44.5	47.0	1.6	1.0	0.40	1.49	0.82	0.082	0.035

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425627
Inside diameter	25.4 mm
Outside diameter	50.005 mm
Thickness	13.495 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE