

Tapered roller bearing 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/16137-16284-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|----------------------|----------------------|-------------------------|-----------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r_a</i> | <i>r_b</i> | <i>C_r</i> | <i>C₁₀</i> | Grease lub. | Oil lub. |
| 34.925 | 72.238 | 20.638 | 20.638 | 19.875 | 3.6 | 1.2 | 49.7 | 61.3 | 5 600 | 7 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer to) | | |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|---------------------------|---------------------------|--------------------|----------------------|----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d_a</i> | <i>d_b</i> | <i>D_a</i> | <i>D_b</i> | <i>r_a</i> max. | <i>r_b</i> max. | <i>e</i> | <i>Y₁</i> | <i>Y₂</i> | Inner ring | Outer ring |
| 16137 | 16284 | 16.6 | 46.5 | 40.5 | 63.0 | 67.0 | 3.6 | 1.2 | 0.40 | 1.49 | 0.82 | 0.236 | 0.144 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426310 |
| Inside diameter | 34.925 mm |
| Outside diameter | 72.238 mm |
| Thickness | 20.638 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE