

Tapered roller bearing 02877-02820-JTEKT - 02877-02820-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/02877-02820-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d _a max.	d _b max.	C _r	C ₁₀	Grease lub.	Oil lub.
34.925	73.025	22.225	22.225	17.462	3.6	3.2	55.0	65.7	5 500	7 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
02877	02820	18.4	48.5	42.0	62.0	68.0	3.6	3.2	0.45	1.32	0.73	0.262	0.158

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426327
Inside diameter	34.925 mm
Outside diameter	43.025 mm
Thickness	22.225 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE