

Tapered roller bearing 3382-3328-JTEKT - 3382-3328-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/3382-3328-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|-------------|--------------------------------------|--|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> ₁ max. | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. | |
| 39.688 | 84.138 | 29.370 | 30.391 | 22.812 | 3.6 | 3.2 | 91.0 | 106 | 5 000 | 6 700 | |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 3382 | 3328 | 18.7 | 52.0 | 45.5 | 72.0 | 76.0 | 3.6 | 3.2 | 0.27 | 2.20 | 1.21 | 0.438 | 0.312 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426723 |
| Inside diameter | 39.688 mm |
| Outside diameter | 84.138 mm |
| Thickness | 29.37 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE