

## Tapered roller bearing 3578R-3520-JTEKT - 3578R-3520-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/3578r-3520-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
44.450	84.138	30.162	30.886	22.812	3.6	3.2	95.8	120	4 600	6 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
3578R	3520	20.5	57.0	51.0	74.0	79.5	3.6	3.2	0.31	1.96	1.08	0.479	0.221

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427058
Inside diameter	44.45 mm
Outside diameter	84.138 mm
Thickness	30.162 mm
Packaging	1
Standard	No standard

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE