

## Tapered roller bearing 46176-46368-JTEKT - 46176-46368-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/46176-46368-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>2</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
44.450	93.662	31.750	31.760	26.195	3.6	3.2	105	134	4 400	5 800

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
46176	46368	24.0	60.0	54.0	79.0	87.0	3.6	3.2	0.40	1.49	0.82	0.609	0.403

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427102
Inside diameter	44.45 mm
Outside diameter	93.662 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE