

## Tapered roller bearing 56418R-56650-JTEKT - 56418R-56650-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/56418r-56650-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	d <sub>a</sub>	d <sub>b</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
106.362	165.100	36.512	36.512	26.988	3.6	3.2	195	325	2 200	2 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to)		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
56418R	56650	38.6	122.0	116.0	149.0	159.0	3.6	3.2	0.50	1.21	0.66	1.84	0.852

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430058
Inside diameter	106.362 mm
Outside diameter	165.1 mm
Thickness	36.512 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE