

# Tapered roller bearing

## JHM522649-JHM522610-JTEKT - JHM522649-JHM522610-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/jhm522649-jhm522610-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	r <sub>3</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
110.000	180.000	47.000	46.000	38.000	3.0	2.5		306	487	2 000	2 700	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
JHM522649	JHM522610	40.6	121.0	125.0	160.0	171.0	3.0	2.5	0.41	1.48	0.81	3.08	1.49

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430256
Inside diameter	110 mm
Outside diameter	180 mm
Thickness	47 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE