

Tapered roller bearing HH228349-HH228310-JTEKT - HH228349-HH228310-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/hh228349-hh228310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
127.000	254.000	77.788	82.560	61.912	9.5	6.4	717	1 050	1 500	2 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HH228349	HH228310	54.3	164.0	148.0	223.0	234.0	9.5	6.4	0.32	1.87	1.03	11.8	6.00

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430485
Inside diameter	127 mm
Outside diameter	254 mm
Thickness	77.788 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE