

Tapered roller bearing LM245846-LM245810-JTEKT - LM245846-LM245810-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/lm245846-lm245810-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
230.188	317.500	47.625	52.388	36.613	3.2	3.2	488	928	970	1 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
LM245846	LM245810	50.5	242.0	238.0	309.0	312.0	3.2	3.2	0.33	1.80	0.99	8.25	2.78

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431819
Inside diameter	230.188 mm
Outside diameter	317.5 mm
Thickness	47.625 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE