

## Needle roller bearing BHTM810-JTEKT - BHTM810-JTEKT

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/bhtm810-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
<b>8</b>	15	10	8.4	4.00	3.30	34 000	<b>BHTM810</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	7.991	8.000	14.977	14.995	6.5	7.3

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952469348
Inside diameter	8 mm
Outside diameter	15 mm
Thickness	10 mm
Weight	6.5 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE