

Needle roller bearing BTM263316A-JTEKT - BTM263316A-JTEKT

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/btm263316a-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|----------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | | |
| | | | | | | | | With open ends | With closed end |
| 25.80 | 33 | 16 | — | 14.2 | 22.4 | 14 000 | BTM263316A | | |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 25.787 | 25.800 | 32.967 | 32.992 | 28 | — |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952471549 |
| Inside diameter | 25.8 mm |
| Outside diameter | 33 mm |
| Thickness | 16 mm |
| Weight | 28 g |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE