

## Roller bearing **NNU4938K-JTEKT - NNU4938K-JTEKT**

<https://www.123bearing.ca/bearing-housing/roller-bearing/roller/nnu4938k-jtekt>

Double-row cylindrical roller bearings **Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i> <i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore	
190	260	69	2	210	405	996	2 000	2 400			

  

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
<b>NNU4938K</b>		199	207	215	251	—	2	11.0	10.5

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473369
Inside diameter	190 mm
Outside diameter	260 mm
Thickness	69 mm
Weight	10500 g
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE