

## Needle roller bearing NQ202823-JTEKT - NQ202823-JTEKT

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nq202823-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) |   |    |    | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|---|----|----|-------------------------|-----------------|--|--------------------|-------------|
| F <sub>w</sub>           | d | D  | B  | C <sub>r</sub>          | C <sub>10</sub> | Oil lub.   | Without inner ring |             |
| 20                       | — | 28 | 23 | 18.4                    | 27.1            | 22 000   | <b>NQ202823</b>    |             |
| Mounting dimensions (mm) |   |    |    | Inlet Mass (kg)         |                 | Inlet  |                    |             |
| With inner ring          |   |    |    | Without inner ring      | With inner ring | Applicable inner ring No.                          |                    |             |
| —                        |   |    |    | 26                      | 0.3             | 0.040  | —                  |             |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 4549250314117 |
| Inside diameter  | 20 mm         |
| Outside diameter | 28 mm         |
| Thickness        | 23 mm         |
| Weight           | 40 g          |
| Packaging        | 1             |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE