

Roller bearing NQ30-20-JTEKT - NQ30-20-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/roller/nq30-20-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
30	—	40	20	—	23.7	37.5	15 000	NQ30/20
Mounting dimensions (mm)				[Refer.] Mass (kg)		[Refer.] Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d_a	D_a	r_a	—	—			
	min.	max.	max.	—	0.066			
	—	38	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482644
Inside diameter	30 mm
Outside diameter	40 mm
Thickness	20 mm
Weight	66 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE