


Roller bearing NA4911R-JTEKT - NA4911R-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/roller/na4911r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | | | |
|--------------------------|----|----|----|-------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|--|--|--|
| F_w | d | D | B | B_1 | C_r | C_{10} | Oil lub. | Grease lub. | Without inner ring | | | | |
| 63 | 55 | 80 | 25 | 1 | 58.4 | 99.0 | 7 300 | — | — | | | | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | | | | |
| NA4911R | | | | | 60 | 75 | 1 | 0.260 | 0.401 | IRM55G325 | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952483665 |
| Inside diameter | 55 mm |
| Outside diameter | 80 mm |
| Thickness | 25 mm |
| Weight | 401 g |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE