

Roller bearing RNA5913-JTEKT - RNA5913-JTEKT

<https://www.123bearing.ca/bearing-housing/roller-bearing/roller/rna5913-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-------|-------|-------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | | Without inner ring | |
| 72 | 65 | 90 | 34 | 85.4 | 158.0 | 6 400 | | RNA5913 | |
| Mounting dimensions (mm) | | | | roller) Mass (kg) | | roller) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d_a | D_a | r_a | 0.419 | 0.813 | IRM657234 | | | |
| | min. | max. | max. | | | | | | |
| | 70 | 85 | 1 | | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952483795 |
| Inside diameter | 72 mm |
| Outside diameter | 90 mm |
| Thickness | 34 mm |
| Weight | 419 g |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE