

Deep groove ball bearing single row 637-ZZ-JTEKT - 637-ZZ-JTEKT

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/single-row/637-zz-jtekt>

Boundary dimensions

Open type Shielded Sealed Locating snap ring

ZZ / 2RS / 2RD 2Z / 2RS / 2RD NR

ISO 7650 / 600 / 620 / 630 / 640 / 650 / 660 / 670 / 680 / 690 / 700 / 710 / 720 / 730 / 740 / 750 / 760 / 770 / 780 / 790 / 800 / 810 / 820 / 830 / 840 / 850 / 860 / 870 / 880 / 890 / 900 / 910 / 920 / 930 / 940 / 950 / 960 / 970 / 980 / 990 / 1000 / 1050 / 1100 / 1150 / 1200 / 1250 / 1300 / 1350 / 1400 / 1450 / 1500 / 1550 / 1600 / 1650 / 1700 / 1750 / 1800 / 1850 / 1900 / 1950 / 2000 / 2050 / 2100 / 2150 / 2200 / 2250 / 2300 / 2350 / 2400 / 2450 / 2500 / 2550 / 2600 / 2650 / 2700 / 2750 / 2800 / 2850 / 2900 / 2950 / 3000 / 3050 / 3100 / 3150 / 3200 / 3250 / 3300 / 3350 / 3400 / 3450 / 3500 / 3550 / 3600 / 3650 / 3700 / 3750 / 3800 / 3850 / 3900 / 3950 / 4000 / 4050 / 4100 / 4150 / 4200 / 4250 / 4300 / 4350 / 4400 / 4450 / 4500 / 4550 / 4600 / 4650 / 4700 / 4750 / 4800 / 4850 / 4900 / 4950 / 5000 / 5050 / 5100 / 5150 / 5200 / 5250 / 5300 / 5350 / 5400 / 5450 / 5500 / 5550 / 5600 / 5650 / 5700 / 5750 / 5800 / 5850 / 5900 / 5950 / 6000 / 6050 / 6100 / 6150 / 6200 / 6250 / 6300 / 6350 / 6400 / 6450 / 6500 / 6550 / 6600 / 6650 / 6700 / 6750 / 6800 / 6850 / 6900 / 6950 / 7000 / 7050 / 7100 / 7150 / 7200 / 7250 / 7300 / 7350 / 7400 / 7450 / 7500 / 7550 / 7600 / 7650 / 7700 / 7750 / 7800 / 7850 / 7900 / 7950 / 8000 / 8050 / 8100 / 8150 / 8200 / 8250 / 8300 / 8350 / 8400 / 8450 / 8500 / 8550 / 8600 / 8650 / 8700 / 8750 / 8800 / 8850 / 8900 / 8950 / 9000 / 9050 / 9100 / 9150 / 9200 / 9250 / 9300 / 9350 / 9400 / 9450 / 9500 / 9550 / 9600 / 9650 / 9700 / 9750 / 9800 / 9850 / 9900 / 9950 / 10000

Example Standard shielded ZZ

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load factor		Limiting speeds (min-1)	
	d	D	B	r (min)	C _r	C _{0r}	C _u	f ₀	Grease lub.	Oil lub.
637 ZZ	7	26	9	0.3	5.65	1.95	0.1	12.3	26000	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060623324
Inside diameter	7 mm
Inside diameter	0.276" inch
Sealing	Shield on both sides
Outside diameter	26 mm
Outside diameter	1.024" inch
Thickness	9 mm
Thickness	0.354" inch
Limiting speed	26000 rpm
Dynamic load	5.65 kN
Static load	1.95 kN
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE